


### AZN 636 ACAR (zincata)

AZN 636 ACAR (galvanized)



#### 265 FILI

6x36WS+IWRC  
anima metallica  
crociata destra  
crociata sinistra

Resistenza 2160 N/mm<sup>2</sup>

#### 265 WIRES

6x36WS+IWRC  
steel core  
right regular lay  
left regular lay

Tensile rope grade 2160 N/mm<sup>2</sup>

Codice Code	Diametro funne Rope diameter	Diametro fili esterni Outer wires diameter	Peso per metro Weight for meter	Carico rottura minimo MBL	
	mm	mm	kg	kN	kg
FZ636R10	10	0,56	0,42	81,80	8340
FZ636R11	11	0,62	0,51	98,90	10090
FZ636R12	12	0,67	0,60	117,80	12010
FZ636R13	13	0,73	0,71	138,30	14100
FZ636R14	14	0,79	0,82	160,30	16350
FZ636R15	15	0,84	0,95	184,00	18760
FZ636R16	16	0,90	1,08	209,50	21360
FZ636R18	18	1,01	1,36	265,00	27020
FZ636R19	19	1,07	1,52	295,00	30080
FZ636R20	20	1,12	1,68	326,50	33290
FZ636R22	22	1,24	2,03	396,00	40370
FZ636R24	24	1,35	2,42	471,50	48070
FZ636R26	26	1,46	2,84	553,00	56380
FZ636R28	28	1,57	3,29	640,00	65240
FZ636R30	30	1,69	3,78	734,00	74830
FZ636R32	32	1,80	4,30	835,50	85170
FZ636R34	34	1,91	4,86	920,00	93790
FZ636R36	36	2,02	5,44	1030,00	105000
FZ636R38	38	2,13	6,06	1150,00	117230
FZ636R40	40	2,25	6,72	1255,00	127940
FZ636R42	42	2,36	7,41	1385,00	141190
FZ636R44	44	2,47	8,13	1515,00	154440
FZ636R46	46	2,58	8,89	1655,00	168710
FZ636R48	48	2,70	9,68	1775,00	180940
FZ636R50	50	2,81	10,50	1926,00	196340
FZ636R52	52	2,92	11,36	2082,00	212240
FZ636R54	54	3,03	12,25	2240,00	228340
FZ636R56	56	3,15	13,17	2370,00	241600
FZ636R58	58	3,26	14,13	2540,00	258920
FZ636R60	60	3,37	15,12	2700,00	275230

