


AZN 636 T (zincata)

AZN 636 T (galvanized)



216 FILI

6x36WS+FC
anima polipropilene
crociata destra

Resistenza 1770 N/mm²

216 WIRES

6x36WS+FC
fiber core
right regular lay

Tensile rope grade 1770 N/mm²

Codice Code	Diametro funne Rope diameter	Diametro fili esterni Outer wires diameter	Peso per metro Weight for meter	Carico rottura minimo MBL	
	mm	mm	kg	kN	kg
FZ636T10	10	0,56	0,37	59,00	6014
FZ636T11	11	0,62	0,44	71,00	7238
FZ636T12	12	0,67	0,53	84,50	8614
FZ636T13	13	0,73	0,62	99,00	10092
FZ636T14	14	0,79	0,72	115,70	11794
FZ636T16	16	0,90	0,94	151,80	15474
FZ636T18	18	1,01	1,19	193,20	19694
FZ636T20	20	1,12	1,48	238,50	24312
FZ636T22	22	1,24	1,79	289,00	29460
FZ636T24	24	1,35	2,13	344,00	35066
FZ636T26	26	1,46	2,50	403,30	41111
FZ636T28	28	1,57	2,90	469,20	47829
FZ636T30	30	1,69	3,33	538,50	54893
FZ636T32	32	1,80	3,78	612,50	62436
FZ636T34	34	1,91	4,27	691,50	70489
FZ636T36	36	2,02	4,79	776,80	79185
FZ636T38	38	2,13	5,34	865,50	88226
FZ636T40	40	2,25	5,92	959,00	97757
FZ636T42	42	2,36	6,52	1047,00	106728
FZ636T44	44	2,47	7,16	1149,70	117197
FZ636T46	46	2,58	7,82	1256,00	128033
FZ636T48	48	2,70	8,52	1368,00	139450
FZ636T50	50	2,81	9,25	1484,00	151274
FZ636T52	52	2,92	10,00	1605,00	163609
FZ636T54	54	3,03	10,78	1732,00	176555
FZ636T56	56	3,15	11,60	1864,00	190010
FZ636T58	58	3,26	12,44	1998,00	203670
FZ636T60	60	3,37	13,32	2135,00	217635

