



COMPACT 9 SR COMPATTATA PARALLELA (zincata)

COMPACT 9 SR COMPACTED STRANDS LANG LAY (galvanized)

| | Codice Code | Diametro funne Rope diameter | Diametro fili esterni Outer wires diameter | Peso per metro Weight for meter | Carico rottura minimo MBL | |
|---|----------------|------------------------------------|--|---------------------------------------|---------------------------------|-------|
| | | mm | mm | kg | kN | kg |
|  <p>112 FILI 9xK7+PWRC anima metallica trefoli compattati parallela destra parallela sinistra Resistenza 2160 N/mm²</p> <p>112 WIRES 9xK7+PWRC steel core compacted strands right lang lay left lang lay Tensile rope grade 2160 N/mm²</p> | FZC09SR06 | 6 | 0,50 | 0,15 | 32,00 | 3260 |
| | FZC09SR07 | 7 | 0,58 | 0,21 | 44,30 | 4490 |
| | FZC09SR08 | 8 | 0,67 | 0,27 | 57,10 | 5810 |
|  <p>202 FILI 9xK17S+PWRC anima metallica trefoli compattati parallela destra parallela sinistra Resistenza 2160 N/mm²</p> <p>202 WIRES 9xK17S+PWRC steel core compacted strands right lang lay left lang lay Tensile rope grade 2160 N/mm²</p> | FZC09SR09 | 9 | 0,60 | 0,35 | 72,00 | 7300 |
| | FZC09SR09,5 | 9,5 | 0,64 | 0,40 | 80,00 | 8160 |
| | FZC09SR10 | 10 | 0,67 | 0,45 | 91,00 | 9290 |
| | FZC09SR11 | 11 | 0,73 | 0,53 | 108,50 | 11070 |
| | FZC09SR12 | 12 | 0,80 | 0,63 | 128,00 | 13060 |
| | FZC09SR13 | 13 | 0,87 | 0,75 | 152,00 | 15500 |
| | FZC09SR14 | 14 | 0,95 | 0,87 | 174,00 | 17750 |
| FZC09SR16 | 16 | 1,08 | 1,14 | 227,30 | 23190 | |

