


Tipo G 4151 GRL-U

Con perno filettato


G 4151 GRL-U type
With screw pin



Tipo G 4153 GRL-UD

Con dado e coppiglia

G 4153 GRL-UD type
With safety bolt



Acciaio alta resistenza gr. 6
Finitura: zincatura a caldo
Gr. 6 high tensile steel
Finish: hot dip galvanized

G 4151 GRL-U	Codice Code	Portata WLL	Misura Size	Dimensioni Dimensions										Peso Weight		
				G 4153 GRL-UD	t	inches	a mm	b mm	c mm	d mm	e mm	f mm	g mm	GRL-U h mm	GRL-UD h mm	j mm
AGRUVF 01	-	1	3/8		10	11	22,5	10	17	32	59	54	-	-	0,14	-
AGRUVF 01,5	-	1,5	7/16		11	13	26,5	11	19	37	68	59,5	-	-	0,19	-
AGRUVF 02	AGRUVD 02	2	1/2		13,5	16	34	13	22	43	81	73	82	13	0,32	0,39
AGRUVF 03,2	AGRUVD 03,2	3,25	5/8		16	19	40	16	27	51	97	89	98	17	0,54	0,67
AGRUVF 04,7	AGRUVD 04,7	4,75	3/4		19	22	46	19	31	59	112	103	114	19	0,87	1,08
AGRUVF 06,5	AGRUVD 06,5	6,5	7/8		22	25	52	22	36	73	134	119	130	22	1,34	1,66
AGRUVF 08,5	AGRUVD 08,5	8,5	1		25	28	59	25	43	85	154	137	150	25	2,08	2,46
AGRUVF 09,5	AGRUVD 09,5	9,5	1 1/8		28	32	66	28	47	90	167	153	166	27	2,77	3,4
AGRUVF 12	AGRUVD 12	12	1 1/4		32	35	72	32	51	94	180	170	178	30	3,72	4,51
AGRUVF 13,5	AGRUVD 13,5	13,5	1 3/8		35	38	80	35	57	115	209	186	197	33	5,14	6,1
AGRUVF 17	AGRUVD 17	17	1 1/2		38	42	88	38	60	127	230	203	202	19	6,85	7,63
AGRUVF 25	AGRUVD 25	25	1 3/4		45	50	103	45	74	149	271	243	249	23	11,45	13,25
AGRUVF 35	AGRUVD 35	35	2		50	57	111	50	83	171	305	272	269	26	16,86	18,53
AGRUVF 42,5	AGRUVD 42,5	42,5	2 1/4		57	65	130	57	95	190	345	310	301	29	24,61	25,94
AGRUVF 55	AGRUVD 55	55	2 1/2		65	70	145	65	105	203	376	344	330	32	32,65	35,33
-	AGRUVD 85	85	3		75	83	162	73	127	229	427	-	380	39	-	52,97

- Coefficiente di sicurezza 6.
- Temperatura di utilizzo: -40°C ÷ 200°C.
- Safety factor 6.
- Temperature range: -40°C ÷ 200°C.

