



T70 1 HALL

Precision at your fingertips

Characteristics

- High-sensitivity proportional push button
- Multiband Radio with Full-Duplex communication
- Highly customizable
- LCD display
- External removable EEPROM SIM module
- Easy and fast maintenance
- High resistance to impacts
- Frequency management against interferences

Specifications

Transmitter	T70 1 HALL
Stop Function	Cat. 3 - PLd
Ingress Protection	IP65/NEMA4
Anti condensation system	na
Frequency Band	Multiband (400 - 930 MHz)
Main Mechanisms (Max. #)	Pushbutton (6)
Auxiliary Mechanisms	Toggle & Rotary switches
Removable EEPROM	External
Battery Model	BT06K
Battery Life	10h (50% Duty Cycle)
Operating Temperature Range	-20C +70C (-4F +158F)
Weight (with Battery) Grams	460
Harness	Hand Strap / Shoulder Strap
Display	2x12 Char LCD
Cable Connection	na
Range Limiter	YES
Associated Receivers	R70/MP10/MR06/MR11/RCANCE/MP08

Associated Applications



HEADQUARTERS

IKUSI - Ángel Iglesias S.A. · Pº Miramón, 170 · 20014 San Sebastián · SPAIN
 Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusitlc.com

IKUSI WORLDWIDE

AUSTRALIA/NEW ZEALAND · BRAZIL · CHILE · COLOMBIA · FRANCE · GERMANY · INDIA · MEXICO · SPAIN · UNITED ARAB EMIRATES

