



T70 2

Multiple configurations on a compact transmitter

Characteristics

- High-sensitivity two-step push button.
- Multiband Radio with Full-Duplex communication
- Highly customizable
- LCD display
- External removable EEPROM SIM module
- Easy and fast maintenance
- High resistance to impacts
- Frequency management against interferences

Specifications

| Transmitter | T70 2 |
|-----------------------------|-------------------------------------|
| Stop Function | Cat. 3 - PLd |
| Ingress Protection | IP65/NEMA4 |
| Anti condensation system | na |
| Frequency Band | Multiband (400 - 930 MHz) |
| Main Mechanisms (Max. #) | Pushbutton (10) |
| Auxiliary Mechanisms | Toggle & Rotary switches |
| Removable EEPROM | External |
| Battery Model | BT06K |
| Battery Life | 10h (50% Duty Cycle) |
| Operating Temperature Range | -20C +70C (-4F +158F) |
| Weight (with Battery) Grams | 550 |
| Harness | Hand Strap / Shoulder Strap |
| Display | 2x12 Char LCD |
| Cable Connection | na |
| Range Limiter | YES |
| Associated Receivers | R70/MP10/MR06/MR11/RCANCE/MP08/MP20 |

Associated Applications



HEADQUARTERS

IKUSI - Ángel Iglesias S.A. · Pº Miramón, 170 · 20014 San Sebastián · SPAIN
Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusitlc.com

IKUSI WORLDWIDE

AUSTRALIA/NEW ZEALAND · BRAZIL · CHILE · COLOMBIA · FRANCE · GERMANY · INDIA · MEXICO · SPAIN · UNITED ARAB EMIRATES

