



IK2

The compact console box

Characteristics

- Up to 2 joysticks or 4 paddles
- Multiband Radio with Full-Duplex communication
- Highly customizable
- 128x64 Graphic LCD
- External removable EEPROM SIM module
- Easy and fast maintenance
- High resistance to impacts
- Innovative ergonomics
- Non-slip handles
- Frequency management against interferences

Specifications

Transmitter	IK2
Stop Function	Cat. 3 - PLd
Ingress Protection	IP65/NEMA4
Anti condensation system	Goretex Film
Frequency Band	Multiband (400 - 930 MHz)
Main Mechanisms (Max. #)	Joystick (2)/Paddle (4)
Auxiliary Mechanisms	Pushbutton, Toggle & Rotary switches
Removable EEPROM	External
Battery Model	BT11K
Battery Life	16h (50% Duty Cycle)
Operating Temperature Range	-20C +70C (-4F +158F)
Weight (with Battery) Grams	950
Harness	Belt / Shoulder Strap
Display	128x64 Graphic LCD
Cable Connection	YES (M12 Connector)
Range Limiter	YES
Associated Receivers	R70/MP10/MR06/MR11/RCANCE/MP08/MP20

Associated Applications



HEADQUARTERS

IKUSI - Ángel Iglesias S.A. · Pº Miramón, 170 · 20014 San Sebastián · SPAIN
 Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusitlc.com

IKUSI WORLDWIDE

AUSTRALIA/NEW ZEALAND · BRAZIL · CHILE · COLOMBIA · FRANCE · GERMANY · INDIA · MEXICO · SPAIN · UNITED ARAB EMIRATES

