



IK4

Service, design and endless options

Characteristics

- Up to 4 joysticks or 8 paddles
- Multiband Radio with Full-Duplex communication
- Highly customizable
- 3.5" color TFT display
- External removable EEPROM SIM module
- Easy and fast maintenance
- High resistance to impacts
- Innovative ergonomics
- Non-slip handles
- Frequency management against interferences

Specifications

Transmitter	IK4
Stop Function	Cat. 3 - PLd
Ingress Protection	IP65/NEMA4
Anti condensation system	Goretex Film
Frequency Band	Multiband (400 - 930 MHz)
Main Mechanisms (Max. #)	Joystick (4)/Paddle (8)
Auxiliary Mechanisms	Pushbutton, Toggle & Rotary switches
Removable EEPROM	External
Battery Model	BT24IK
Battery Life	16h (50% Duty Cycle)
Operating Temperature Range	-20C +70C (-4F +158F)
Weight (with Battery) Grams	2300
Harness	Belt / Shoulder Strap
Display	3.5" Colour TFT
Cable Connection	YES (M12 Connector)
Range Limiter	YES
Associated Receivers	R70/R70PLUS/MR11/RCANCE/MP20

Associated Applications



HEADQUARTERS

IKUSI - Ángel Iglesias S.A. · Pº Miramón, 170 · 20014 San Sebastián · SPAIN
Tel.: +34 943 44 88 00 · Fax: +34 943 44 88 20 · tlc@ikusi.com · www.ikusitlc.com

IKUSI WORLDWIDE

AUSTRALIA/NEW ZEALAND · BRAZIL · CHILE · COLOMBIA · FRANCE · GERMANY · INDIA · MEXICO · SPAIN · UNITED ARAB EMIRATES

