

B-ABA



Lifting point that can be loaded on all sides.



PRODUCT FEATURES

- Large WLL range 1.6 t–31.5 t.
- No rattling noise or shaking even with strong vibrations or shocks loads, easy connection of the lifting means possible.
- ICE-Bolt made from patented steel. Safe deep temperature usage; improved toughness meaning higher bending strength and lower wear occurrence.
- Patented wear markings inside and out.
- Clear marking of the minimum WLL.



<p>No rattling noise or shaking.</p>	<p>ICE-Bolt made from patented steel.</p>	<p>Clear marking.</p>
<p>WLL X</p> <p>X WLL</p>	<p>WLL Y</p> <p>Y=1X WLL</p>	<p>WLL Z</p> <p>Z=1X WLL</p>



✓ Tested and certified by DGVU.
 Test criteria: GS-OA-15-04: 2015-12
 Certificate no.: OA 1651055

- Can be loaded from all sides.
- 4-times the safety against breakage.
- Tempered main body, making it more wear resistant.

B-ABA

Metric thread.

B-ABA – LIFTING POINT THAT CAN BE LOADED ON ALL SIDES.

Type	WLL [t]	Weight (kg/unit)	T [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	G [mm]	H [mm]	L [mm]	M	Tightening torque [Nm]	Ref. No.
B-ABA 1.6t	1.6	0.88	46.5	75	16	100	35	16	62.5	55	55	13	4×M10	55	7906266
B-ABA 3.2t	3.2	2	65	92	23	137	50	21	86	70	75	16	4×M12	100	7906267
B-ABA 5t	5	4.1	80	113	27	172	60	28	108	84	95	24	4×M16	240	7906268
B-ABA 10t	10	9.3	105	146	38	228	80	36	141	110	125	25	4×M20	450	7906269
B-ABA 20t	20	18.8	148	200	52	272	115	40	188	150	75	30	6×M24	800	7906270
B-ABA 31.5t	31.5	29.5	170	230	64	320	130	50	220	175	87.5	40	6×M30	950	7906271

Subject to technical changes!

