




MODEL L

LOCKING TYPE

Suitable up to 90° lateral WLL. Each clamp is tested for 2 x WLL, provided with a serial number, and is delivered with a certificate and CE-marking. Safety factor 3:1.

Suitable up to a sheet surface hardness of 363 HV 10 (341 HB / 37 RC). Made of high strength steel. Each clamp is given a RFID transponder as standard, for simplified inspection and documentation. L-vertical clamps are equipped with a lever for locking the open and closed position. Area of application temperature: -20 °C to 100 °C (ambient and load temperature). The L-clamps are compact and easy to operate. The construction design of the L-clamps allows simple repair and maintenance.



Type	Mat. no.	W.L.L.	Kg	T (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	J (mm)	K (mm)
L 0,5 t	8505240	0,5 t	1,99	214	0-16	51	124	206	29	114	62	35	13	14.3
L 1 t	8505241	1 t	2,26	214	0-19	51	124	206	29	114	62	35	13	14.3
L 2 t	8505242	2 t	8,86	339	0-25	84	175	318	60	184	92	60	16	20.6
L 3 t	8505243	3 t	14,69	428	0-25	84	254	414	92	216	97	70	19	25.4