

# VABH-W / VCGH-S

4:1

-40°  
200°C-20°  
200°C400°C  
max.

(1)

(2)

VIP-weld-on-block.



VABH-W (1)



VCGH-S (2)

## PRODUCT FEATURES

- Large WLL range 1.5 t – 20 t.
- For combination with all conventional lifting means without additional connecting elements.
- Patented wear markings for easy determination of wear.
- Robust forged safety latch.
- Phosphated surface.
- VABH-W also for use an excavator hook.
- Simple and fast welding installation.



✓ Corresponds with the test criteria of BG/DGUV "GS-OA-15-04".

- As a weld-on point on trusses and beams.
- For ropes and round slings.
- For lifting means with eye or oval ring.

# VABH-W / VCGH-S

## Technical data.

### VABH-W – VIP-WELD-ON-BLOCK.

Type	WLL [t]	Weight (kg/unit)	T [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	I [mm]	Welding seam	Ref. No.
VABH-W 1.5t	1.5	0.8	26	7.5	76	115	111	70	26	38	a4	7991208
VABH-W 2.5t	2.5	1.8	33	8.5	98	148	143	85	31.5	49	a5	7991209
VABH-W 4t	4	3.12	40	12	119	168	164	104	35	59	a6	7991210
VABH-W 6.7t	6.7	5.89	51	13	147	205	200	120	40	70	a6	8502239

Subject to technical changes!

### VCGH-S – VIP-WELD-ON-BLOCK.

Type	WLL [t]	Weight (kg/unit)	T [mm]	A [mm]	B [mm]	C [mm]	D [mm]	E [mm]	F [mm]	I [mm]	Welding seam	Ref. No.
VCGH-S 16	10	5.67	49	15	141	200	220	100	48	69	a8	7984047
VCGH-S 20	16	8.4	69	20	187	272	288	120	63	87	a8	7984310
VCGH-S 22	20	14.5	74	20	196	276	292	120	63	92	a8	7984312

Subject to technical changes!

