

# HBEP

ELECTRO PERMANENT LIFTING MAGNETS WITH BATTERY SUPPLY FOR LIFTING FLATS AND ROUNDS






### MAXIMUM SAFETY

The magnet is activated by a short current pulse. The effective force is generated by permanent magnets. The safety factor of 3 guarantees safe operation, even with rough and dirty workpieces.



#### **ENERGY FRIENDL**

95% less energy consumption than traditional electromagnets. A short current pulse is enough to activate / deactivate the magnet. The powerful rechargeable battery guarantees >1000 cycles before charging.



No power cable required. Manual operation by using the magnet's control panel. **NEW!** Automatic switching between MAG and DEMAG via the proximity switch.

The proximity switch prevents demagnetization in the air and starts the MAG and DEMAG cycle when AUTO-cycle selected.



- Safety factor 3:1
- 6 models from 500 kg to 5000 kg
- Lithium battery technology with high autonomy
- Manual or automatic operation
- 4 Levels PICK-UP force for lifting 1 single steelsheet from a stack.
- Proximity switch against accidental demagnetization in the air.

MODEL		WEIGHT (KG)	VOLTAGE (V)	DIMENSIONS (LxWxH)	MIN. MATERIAL THICKNESS (MM)	SWL FLAT MAX (KG)	SWL ROUND MAX (KG)
	HBEP-005	51	60	370x190x382	4	500	250
	HBEP-010	73	60	370x240x402	6	1000	500
	HBEP-015	88	60	426x240x417	6	1500	750
	HBEP-020	118	60	470x330x404	8	2000	1000
	HBEP-030	185	60	638x346x427	10	3000	1500
	HBEP-050 * Lead-Acid battery	502	72	1332x547x530	20	5000	2500



### **BATTERY POWERED** ELECTRO PERMANENT LIFTING MAGNETS



# SERIE: HBEP

Lifting of Flat and Round Steel Parts 500 kg—5.000 Kg



SERIE: HBEPP Lifting of single steel Sheets ≥ 5 mm 3—6—9—12—16 m 1.000 kg—25.000 kg



SERIE: HBEPS Lifting HEA-HEB-IPE-IPN 80-600 Profiles 3—6—12—18—24 m 1.300 kg—5.200 kg

## · 100% Safe

- · Force is generated by permanent Magnets
- No heating of the Magnet
- · Predictable and constant Force
- More than 95% Energy savings
- · No back-up Batteries required
- No residual magnetism in the Material
- No interferences with electronical Device
- · No Maintenance

# ELECTRO PERMANENT LIFTING MAGNETS (400V-50Hz)



SERIE: HM1-FIX BEAM Lifting of single steel Sheets ≥ 5 mm 3—6—9—12—16 m







TÜV

2.500 kg-24.000 kg SERIE: HM2-TELESCOPIC BEAM

Lifting of single steel Sheets ≥ 5 mm 12m—16 m 5.000 kg—24.000 kg

# SERIE: HM3

Lifting of THIN steel Sheets ≥ 3 mm 3—6—9—12 m 1.000 kg-4.000 kg

SERIE: HM4 Vertical lifting of steel Sheets 6—12—16 m Dimensions/capacities on request

SERIE: HM5 Uncharging of cutting machines in one movement. Dimensions/capacities on request



### SERIE: HM6

Lifting of multiple steel sheets Dimensions/capacities on request

SERIE: HS Lifting HEA-HEB-IPE-IPN 80-600 Profiles 3—6—12—18—24 m 1.300 kg—5.200 kg

SERIE: HT Lifting of cilindrical steelparts (single and rows) Dimensions/capacities on request

SERIE: HC Lifting of coils Horizontal or vertical Eye Dimensions/capacities on request

SERIE: HB Lifting of Billets and Slabs Dimensions/capacities on request

