

OVAL PATTERN CONSTRUCTION BLOCKS



- All blocks are galvanized.
- Assembled with self lubricated bronze bushing.
- Combines weight of regular oval blocks with strength of extra heavy oval blocks.
- · Assembled with bolt type anchor shackle.
- Sheave lubricated through pressure lube fitting in center pin. Side plates are rounded to provide additional stiffness and reduce wear and chaffing of the rope.

Q-681-Z / Q-682-Z / Q-683-Z

Block Size (in)	Stock No.Bronze Bushed Steel Sheaves						
DIOCK Size (III)	Q-681-Z	Q-682-Z	Q-683-Z				
6	760441	760665	-				
6	760452	760676	760812				
8	760463	760687	760823				
10	760474	760698	760834				

Q-681-Z / Q-682-Z / Q-683-Z

	Sheave Dimensions (mm)			Wire Rope	Working Load Limit (t)		Weight Each (kg)			
Block Size (in)	Outside Diam.	Rim Thickness	Center Pin Dia.	Diameter (mm)	Single	Double	Triple	Single	Double	Triple
6	152	25.4	19.1	10	2.70	3.63	-	6.8	12.7	14.5
6	152	25.4	19.1	13	2.70	3.63	4.50	7.3	12.7	14.5
8	203	31.8	25.4	16	3.63	5.44	-	13.2	20.4	28.1
10	254	31.8	25.4	16	3.63	6.35	7.25	17.2	27.7	36.3

^{4:1} Design Factor

346